

Microestil® DECO-PAST OXIDO



PRODUCT INFORMATION

Custom paste coating for creating rust-effect glazes. Quick and easy application. Supplied in ready-to-use paste. Without Potlife.

TECHNICAL DATA OF APPLICATION

Product description	One-component, ready-to-use paste coating, suitable for creating rust-effect glazes on smooth cement, plaster, concrete and wood surfaces. Inside.		
Surface preparation	The surface must have a minimum resistance of 1.5 N / mm ² , it must be clean, free of cracks, traces of oil, grease and paints as well as any contaminant that may prevent a correct adhesion to the support. On microcement surfaces, they must be sanded and clean.		
Colour	GOLD, BRONZE Y COOPER.		
Conservation	One year from its date of manufacture, in its original package, unopened, indoors and avoiding frost. Do not store directly in the sun.		
Package	<table border="1"> <tr> <td>Pot</td> </tr> <tr> <td>1kg</td> </tr> </table>	Pot	1kg
Pot			
1kg			
Consumption	7-10m ² / Kg		
Use	<p>Before using DECO-PAST OXIDO, stir with a trowel or similar. Apply a thin layer with a stainless steel or plastic trowel a first layer of DECO-PAST OXIDO, the product allows applications fresh on fresh or fresh on dry, achieving different effects. To carry out applications with a brush or roller, dilute with 5% water.</p> <p>Do not open the container for a long time. Do not add water or additives that modify the product.</p>		



Microestil® DECO-PAST OXIDO



Technical data	Finish: Oxide
Application conditions	The ambient temperature must be between 10°C and 25°C.
Dry	To touch: 30 minutes Sealing: 12-24h
Cleaning	After using the tools, they should be cleaned immediately with water.
Cautions	When applying the product, adopt appropriate individual protection measures for the use indicated in this technical sheet, protect the skin and eyes. In case of contact, rinse with plenty of water. In case of contact with the eyes, also visit a doctor. Once hardened it is harmless. Professional use.

Note: This technical data sheet serves, like all other recommendations and technical information, only to describe the characteristics of the product, how to use it and its applications. The data and information reproduced are based on our technical knowledge obtained in the literature, laboratory tests and in practice. The data on consumption and dosage that appear in this technical sheet are based on our own experience, so these are susceptible to variations due to the different conditions of the works. The actual consumptions and dosages must be determined on site, by means of previous tests and are the responsibility of the client. For additional advice consult our technical service. Microestil Cement, s.l. reserves the right to modify the composition of the products, as long as they continue to fulfill the characteristics described in the technical sheet. Other applications of the product that do not conform to those indicated, will not be our responsibility. We grant a guarantee in the event of manufacturing quality defects of our products, excluding additional claims, being our sole responsibility to re-enter the value of the merchandise supplied. This data sheet loses its validity with the appearance of a new edition.