

ESACID S-10



PRODUCT INFORMATION

Cleaner to remove soluble salts and efflorescence. Poolcem System.

DATOS TÉCNICOS DE APLICACIÓN	
Product description	Cleaner to remove soluble salts and efflorescence in concrete and mortar, avoiding problems of adhesion to the support and between coats of product applied.
Properties	ESACID S -10 does not contain organic solvents and heavy metals and they are free of phosphates. It is biodegradable and only produces a light environmental impact.
Conservation	1 year from the manufacture date, into the original package, closed, under cover, and avoiding frost and direct sunlight.
Package	Package 5 Kg 10 Kg
Consumption	0.25g/m2
Aplication	Dampen the support with water prior to treatment; ESACID S-10 must not get into the support, only to act on the surface. Apply ESACID S-10 spray evenly, then rub the surface with a non-metallic bristle brush and rinse with water, better with high pressure water. You can repeat the operation if necessary. ESACID S-10 is a product ready for apply, although they must be done dilutions with water to 100% depending of the type of support.
Sewage treatment	All sewage must be treated according national law and local regulations in force prior to be poured to sewer.
Cautions	Avoid direct skin contact. Use gloves and goggles during application. In case of eyes contact, skin or mucous membranes, wash immediately with clean water and consult a doctor. For more information request the Safety Data Sheet.

NOTE: this technical datasheet serves as all other recommendations and technical information, is to describe the product characteristics, mode of use and applications. The information supplied is based on our technical knowledge obtained in the bibliography, laboratory tests and in practice. The data about consumption and dosage contained in this datasheet is based upon extensive experience so these are susceptible to variations due to the different conditions of work. Real consumption and dosages should be decided on -site through preliminary tests and are the responsibility of the customer. For further advice contact our technical service. Microestil Cement, SL reserves the right to update and change the composition of the products, excluding any other complaints, only to be our responsibility to return the value of the goods supplied. The present technical datasheet loses your validity with the appearance of a new edition.

