

# ESACRIL



## PRODUCT INFORMATION

Microcement resin BC

### TECHNICAL DATA OF APPLICATION

Area of application	Microestil® microcements BC System				
Product Description	Acrylic resin based on water specially developed for the production of two-component (BC) microcement high strength. Improving flexibility, hardness, chemical and mechanical resistance.				
Colour	Colour White.				
Conservation	Approx. 12 months in dry places into their original package.				
Package	<table border="1"> <tr> <th>Pot</th> </tr> <tr> <td>1 lts.</td> </tr> <tr> <td>5 lts.</td> </tr> <tr> <td>10 lts.</td> </tr> </table>	Pot	1 lts.	5 lts.	10 lts.
Pot					
1 lts.					
5 lts.					
10 lts.					
Use	Mixing ratio, Microestil® microcement BC System: BC BASE 25Kg : 7,5Lts de resin ESACRIL BC MEDIO 20Kg : 7,4Lts de resin ESACRIL BC FINO 20Kg : 9Lts de resin ESACRIL BC DUR 20KG: 5,2LTS de resin ESACRIL				
Technical Features	Chemical description: Acrylic copolymer Form: liquid Smell: light pH value: 7,5 – 8,5 (DIN ISO 976) Solid content: 30-31%				
Cleaning	After using the tools should be cleaned immediately with water.				
Cautions	Use resistant protective chemicals gloves. Wear safety glasses with side protection (with frame). Wash hands and / or face before breaks and after to finish work .Avoid contact with the eyes and skin. Use personal protection clothes. Consult the Safety Technical Datasheet.				

NOTE: this technical datasheet serves as all other recommendations and technical information, is to describe the product characteristics, mode of use and applications. The information supplied is based on our technical knowledge obtained in the bibliography, laboratory tests and in practice. The data about consumption and dosage contained in this datasheet is based upon extensive experience so these are susceptible to variations due to the different conditions of work. Real consumption and dosages should be decided on -site through preliminary tests and are the responsibility of the customer. For further advice contact our technical service. Microestil Cement, SL reserves the right to update and change the composition of the products. Other product applications that do not conform to those indicated will not be our responsibility. We give guarantee in case of manufacturing defects quality of our products, excluding any other complaints, only to be our responsibility to return the value of the goods supplied. The present technical datasheet loses your validity with the appearance of a new edition.

