



Microestil V100



PRODUCT INFORMATION

Glass Microspheres for antislip finish on industrial and decorative pavements.

TECHNICAL DATA OF APPLICATION

Product description	Glass Microspheres for antislip finish on industrial and decorative pavements.	
Area of application	Microestil V100 is used; in combination with varnishes or resins for obtain finishes with antislip texture in pavements. It permits transparent or coloured finishes of antislip texture on microcement, levelings and concrete.	
Properties	This increase the resistance of striped and slipping of pavement. Size grain: 90% between 75 and 150 microns.	
Material base	Microestil V100 is a material bought by glass colourless microspheres	
Package	Package	Pot 1 Kg.
Use	Add to the varnish in rate 5 to 10% above weight the varnish, during application is necessary to shake the varnish to prevent settle.	

NOTE: this technical datasheet serves as all other recommendations and technical information, is to describe the product characteristics, mode of use and applications. The information supplied is based on our technical knowledge obtained in the bibliography, laboratory tests and in practice. The data about consumption and dosage contained in this datasheet is based upon extensive experience so these are susceptible to variations due to the different conditions of work. Real consumption and dosages should be decided on -site through preliminary tests and are the responsibility of the customer. For further advice contact our technical service. Microestil Cement, SL reserves the right to update and change the composition of the products. Other product applications that do not conform to those indicated will not be our responsibility. We give guarantee in case of manufacturing defects quality of our products, excluding any other complaints, only to be our responsibility to return the value of the goods supplied. The present technical datasheet loses your validity with the appearance of a new edition.